

CE EMC Test Report



(Declaration of Conformity)

For
Electromagnetic Interference

Of

Product : 150W Enclosed Power Supply

Trade Name : 

Model Number : ESE150-12M, ESE150-24M, ESE150-36M,
ESE150-48M

Prepared for

Eaglerise Electronics (Foshan) Co., Ltd.

No.4, East Huanzhen Road, Beijiao, Shunde, Foshan, Guangdong, 528000, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : Eaglerise Electronics (Foshan) Co., Ltd.
Address : No.4, East Huanzhen Road, Beijiao, Shunde, Foshan,
Guangdong, 528000, China

Manufacturer's Name : Eaglerise Electronics (Foshan) Co., Ltd.
Address : No.4, East Huanzhen Road, Beijiao, Shunde, Foshan,
Guangdong, 528000, China

Product description

Product name : 150W Enclosed Power Supply
Model and/or type reference : ESE150-12M, ESE150-24M, ESE150-36M, ESE150-48M

Standards : EN 55022:2010 EN 55024:2010
EN 55011:2009 EN 61000-6-2:2005
EN 61000-3-2:2006+A1:2009+A2:2009
EN 61000-3-3:2008

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the 2004/108/EC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test :
Date (s) of performance of tests : 22 Nov. 2012 ~04 Dec. 2012
Date of Issue : 04 Dec. 2012
Test Result : **Pass**

Testing Engineer : Apple Huang
(Apple Huang)

Technical Manager : Jim He
(Jim He)

Authorized Signatory : Bovey Yang
(Bovey Yang)

Table of Contents	Page
1 . TEST SUMMARY	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 DESCRIPTION OF TEST SETUP	10
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	11
2.5 MEASUREMENT INSTRUMENTS LIST	12
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION	14
3.1.2 TEST PROCEDURE	15
3.1.3 TEST SETUP	15
3.1.4 EUT OPERATING CONDITIONS	15
3.1.5 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	18
3.2.2 LIMITS OF RADIATED EMISSION MEASUREMENT	18
3.2.3 TEST PROCEDURE	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	19
3.2.6 TEST RESULTS	20
3.2.7 TEST RESULTS(1000~6000MHz)	22
3.3 HARMONICS CURRENT	23
3.3.1 LIMITS OF HARMONICS CURRENT	23
3.3.1.1 TEST PROCEDURE	24
3.3.1.2 EUT OPERATING CONDITIONS	24
3.3.1.3 TEST SETUP	24
3.3.2 TEST RESULTS	25
3.4 VOLTAGE FLUCTUATION AND FLICKERS	31
3.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKERS	31
3.4.1.1 TEST PROCEDURE	31
3.4.1.2 EUT OPERATING CONDITIONS	31
3.4.1.3 TEST SETUP	31
3.4.2 TEST RESULTS	32

Table of Contents	Page
4 . EMC IMMUNITY TEST	33
4.1 STANDARD COMPLIANCE/SERVIRTY LEVEL/CRITERIA	33
4.2 GENERAL PERFORMANCE CRITERIA	34
4.3 GENERAL PERFORMANCE CRITERIA TEST SETUP	34
4.4 ESD TESTING	35
4.4.1 TEST SPECIFICATION	35
4.4.2 TEST PROCEDURE	35
4.4.3 TEST SETUP	36
4.4.4 TEST RESULTS	37
4.4.5 PHOTO(S) SHOWN THE LOCATION(S) OF ESD EVALUATED	38
4.5 RS TESTING	39
4.5.1 TEST SPECIFICATION	39
4.5.2 TEST PROCEDURE	39
4.5.3 TEST SETU	40
4.5.4 TEST RESULTS	41
4.6 EFT/BURST TESTING	42
4.6.1 TEST SPECIFICATION	42
4.6.2 TEST PROCEDURE	42
4.6.3 TEST SETUP	43
4.6.4 TEST RESULTS	44
4.7 SURGE TESTING	45
4.7.1 TEST SPECIFICATION	45
4.7.2 TEST PROCEDURE	45
4.7.3 TEST SETUP	46
4.7.4 TEST RESULTS	47
4.8 INJECTION CURRENT TESTING	48
4.8.1 TEST SPECIFICATION	48
4.8.2 TEST PROCEDURE	48
4.8.3 TEST SETUP	49
4.8.4 TEST RESULTS	50
4.9 POWER FREQUENCY MAGNETIC FIELD TESTING	51
4.9.1 TEST SPECIFICATION	51
4.9.2 TEST PROCEDURE	51
4.9.3 TEST SETUP	52
4.9.4 TEST RESULTS	53
4.10 VOLTAGE INTERRUPTION/DIPS TESTING	54
4.10.1 TEST SPECIFICATION	54
4.10.2 TEST PROCEDURE	54
4.10.3 TEST SETUP	54

Table of Contents	Page
4.10.4 TEST RESULTS	55
5 . EUT TEST PHOTO	56
ATTACHMENT PHOTOGRAPHS OF EUT	58

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
EN 55022:2010 EN 55011:2009	Conducted Emission On AC And Telecom Port 150kHz to 30MHz	Class B	PASS	
	Radiated Emission 30MHz to 1000MHz	Class B	PASS	
	Radiated Emission 1GHz to 6GHz	Class B	N/A	NOTE (1)
EN61000-3-2:2006+A2:2009	Harmonic Current Emission	Class A or D NOTE (2)	PASS	
EN 61000-3-3:2008	Voltage Fluctuations & Flicker	-----	PASS	
EMC Immunity				
Section EN 55024:2010 EN 61000-6-2:2005	Test Item	Performance Criteria	Judgment	Remark
EN 61000-4-2:2009	Electrostatic Discharge	B	PASS	
EN 61000-4-3:2006+A1:2008+A2:2010	RF electromagnetic field	A	PASS	
EN 61000-4-4:2012	Fast transients	B	PASS	
EN 61000-4-5:2006	Surges	B	PASS	
EN 61000-4-6:2012	Injected Current	A	PASS	
EN 61000-4-8:2010	Power Frequency Magnetic Field	A	PASS	
EN 61000-4-11:2004	Volt. Interruptions Volt. Dips	B / C / C NOTE (3)	PASS	

NOTE:

- (1) If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.
If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.
If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, measurement shall only be made up to 5 GHz.
If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.
- (2) The power consumption of EUT is less than 75W and no Limits apply.
- (3) Voltage dip: 100% reduction – Performance Criteria **B**
Voltage dip: 30% reduction – Performance Criteria **C**
Voltage Interruption: 100% Interruption – Performance Criteria **C**
- (4) For client's request and manual description, the test will not be executed.
- (5) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd.

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration Number: 238937; IC Registration Number: 9270A-1

CNAS Registration Number: L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~6GHz	5.0	

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	150W Enclosed Power Supply				
Model Name	ESE150-12M				
Serial No	ESE150-24M, ESE150-36M, ESE150-48M				
Model Difference	All models are identical except model names, output voltage and the technical parameter of secondary parts and components.				
Product Description	<p>The EUT is a 150W Enclosed Power Supply.</p> <table border="1" data-bbox="598 824 1390 891"> <tr> <td>Operating frequency:</td> <td>N/A</td> </tr> <tr> <td>Connecting I/O port:</td> <td>N/A</td> </tr> </table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operating frequency:	N/A	Connecting I/O port:	N/A
Operating frequency:	N/A				
Connecting I/O port:	N/A				
Power Source	AC Voltage				
Power Rating	Input: 200-240V~ Output: 12V, 12.5A				

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Full Load


For Conducted Test	
Final Test Mode	Description
Mode 1	Full Load

For Radiated Test	
Final Test Mode	Description
Mode 1	Full Load

For EMS Test	
Final Test Mode	Description
Mode 1	Full Load

2.3 DESCRIPTION OF TEST SETUP

Mode :



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	150W Enclosed Power Supply		ESE150-12M	N/A	EUT
E-2	Load	N/A	0.96R	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	30cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” “with core”; “NO” means “unshielded” “without core”.

2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101313	Jul. 06, 2013
2	LISN	EMCO	3816/2	00042990	Jul. 06, 2013
3	50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 06, 2013
4	Test Cable	N/A	C01	N/A	Jul. 06, 2013
5	Test Cable	N/A	C02	N/A	Jul. 06, 2013
6	Test Cable	N/A	C03	N/A	Jul. 06, 2013
7	EMI Test Receiver	R&S	ESCI	101160	Jul. 06, 2013
8	Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 06, 2013
9	Triple-Loop Antenna	EVERFINE	LIA-2	11020003	Jul. 06, 2013
10	Absorbing Clamp	R&S	MDS-21	100423	Jul. 08, 2013

2.5.2 RADIATED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06, 2013
2	Test Cable	N/A	R-01	N/A	Jul. 06, 2013
3	Test Cable	N/A	R-02	N/A	Jul. 06, 2013
4	EMI Test Receiver	R&S	ESCI-7	101318	Jul. 06, 2013
5	Antenna Mast	EM	SC100_1	N/A	N/A
6	Turn Table	EM	SC100	060531	N/A
7	50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 06, 2013
8	Spectrum Analyzer	Aglient	E4407B	MY45108040	Jul. 06. 2013
9	Horn Antenna	EM	EM-AH-1018 0	2011071402	Jul. 06. 2013
10	Amplifier	EM	EM-30180	060538	Jul. 06. 2013

2.5.3 HARMONICS AND FILCK

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Harmonic & Flicker	EM TEST	DPA500	0303-04	Jul. 06, 2013
2	AC Power Source	EM TEST	ACS500	0203-01	Jul. 06, 2013

2.5.4 ESD

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	ESD TEST GENERATOR	SCHAFFNER	NSG438	859	Jul. 06, 2013

2.5.5 RS

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Signal Generator	R&S	SMT 06	832080/007	Jul. 24, 2013
2	Log-Bicon Antenna	Schwarzbeck	VULB9161	4022	Aug. 15, 2013
3	Power Amplifier	AR	150W1000M1	320946	Sep. 23, 2013
4	Microwave Horn Antenna	AR	AT4002A	321467	Jun. 11, 2013
5	Power Amplifier	AR	25S1G4A	308598	Sep. 23, 2013

2.5.6 SURGE, EFT/BURST, VOLTAGE INTERRUPTION/DIPS

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Surge Generator	EVERFINE	EMS61000-5 A	1101002	Jul. 06, 2013
2	DIPS Generator	EVERFINE	EMS61000-1 1K	1011002	Jul. 06, 2013
	EFT/B Generator	EVERFINE	EMS61000-4 A-V2	1012005	Aug. 04, 2013

2.5.7 INJECTION CURRENT

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Signal Generator	IFR	2023A	202301/368	Mar. 31, 2013
2	Power Amplifier	AR	75A250AM1	0320709	Sep. 23, 2013
3	CDN	FCC	FCC-801-M2	06043	Jun. 02, 2013
4	EM Clamp	FCC	F-203I-23MM	504	Jun. 09, 2013

2.4.8 MF

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Generator	EVERFINE	EMS61000-8 K	1007001	Jul. 06, 2013

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name. :	ESE150-12M
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2012-11-29
Test Mode :	Full Load	Phase :	L
Test Voltage :	AC 230V/50Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.1539	48.76	9.82	58.58	79	-20.42	QP
0.158	41.16	9.81	50.97	66	-15.03	AVG
0.23	24.68	9.81	34.49	66	-31.51	AVG
0.234	33	9.82	42.82	79	-36.18	QP
8.058	25.26	10.39	35.65	73	-37.35	QP
8.134	19.09	10.39	29.48	60	-30.52	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	150W Enclosed Power Supply	Model Name. :	ESE150-12M
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2012-11-29
Test Mode :	Full Load	Phase :	N
Test Voltage :	AC 230V/50Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.1539	48.06	9.85	57.91	79.00	-21.09	QP
0.1580	39.29	9.88	49.17	66.00	-16.83	AVG
2.9420	11.14	10.29	21.43	60.00	-38.57	AVG
8.5219	15.37	10.33	25.7	60.00	-34.30	AVG
8.9100	21.45	10.33	31.78	73.00	-41.22	QP
24.3220	28.04	10.56	38.6	73.00	-34.40	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT (Below 1000MHz)

FREQUENCY (MHz)	Class A		Class B	
	At 10m	At 3m	At 10m	At 3m
	dBuV/m	dBuV/m	dBuV/m	dBuV/m
30 – 230	40	50	30	40
230 – 1000	47	57	37	47

3.2.2 LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (at 3m) dBuV/m		Class B (at 3m) dBuV/m	
	Peak	Avg	Peak	Avg
1000-3000	76	56	70	50
3000-6000	80	60	74	54

Notes:


- (1) The limit for radiated test was performed according to as following:
CISPR 22.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.3 TEST PROCEDURE


- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP(AV) Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.2.6 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-11-29
Test Mode :	Full Load	Polarization :	Horizontal
Test Power :	AC 230V/50Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
83.2298	23.02	8.36	31.38	50	-18.62	QP
213.0151	19.2	9.82	29.02	50	-20.98	QP
651.9417	8.01	23.46	31.47	57	-25.53	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-11-29
Test Mode :	Full Load	Polarization :	Vertical
Test Power :	AC 230V/50Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
30.3173	10.81	18.19	29	50	-21	QP
84.11	23.47	8.53	32	50	-18	QP
151.0666	14.12	11.68	25.8	50	-24.2	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit



3.2.7 TEST RESULTS(1000~6000MHz)

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	N/A
Test Mode :	N/A	Polarization :	N/A
Test Power :	N/A		

3.3 HARMONICS CURRENT

3.3.1 LIMITS OF HARMONICS CURRENT

IEC 555-2					
Table - I			Table - II		
Equipment Category	Harmonic Order n	Max. Permissible Harmonic Current (in Amperes)	Equipment Category	Harmonic Order n	Max. Permissible Harmonic Current (in Amperes)
Non Portable Tools or TV Receivers	Odd Harmonics		TV Receivers	Odd Harmonics	
	3	2.30		3	0.80
	5	1.14		5	0.60
	7	0.77		7	0.45
	9	0.40		9	0.30
	11	0.33		11	0.17
	13	0.21		13	0.12
	15 ≤ n ≤ 39	0.15 · 15/n		15 ≤ n ≤ 39	0.10 · 15/n
	Even Harmonics			Even Harmonics	
	2	1.08		2	0.30
	4	0.43		4	0.15
	8	0.30			
8 ≤ n ≤ 40	0.23 · 8/n	DC	0.05		

EN 61000-3-2/IEC 61000-3-2					
Equipment Category	Max. Permissible Harmonic Current (in Amperes)	Equipment Category	Harmonic Order n	Max. Permissible Harmonic Current (in A)	Max. Permissible Harmonic Current (mA/w)
Class A	Same as Limits Specified in 4-2.1, Table - I, but only odd harmonics required	Class D	3	2.30	3.4
			5	1.14	1.9
			7	0.77	1.0
			9	0.40	0.5
			11	0.33	0.35
			13 ≤ n ≤ 39	see Table I	3.85/n

3.3.1.1 TEST PROCEDURE

a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions.

b. The classification of EUT is according to section 5 of EN 61000-3-2. The EUT is classified as follows:

Class A: Balanced three-phase equipment, Household appliances excluding equipment as Class D, Tools excluding portable tools, Dimmers for incandescent lamps, audio equipment, equipment not specified in one of the three other classes.

Class B: Portable tools. Portable tools.; Arc welding equipment which is not professional equipment.

Class C: Lighting equipment.


Class D: Equipment having a specified power less than or equal to 600 W of the following types: Personal computers and personal computer monitors and television receivers.

c. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

3.3.1.2 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.1.3 TEST SETUP



3.3.2 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-11-29
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

E. U. T. Result

Harmonic(s) > 200%:	
Order (n):	None
Harmonic(s) with average > 90%:	
Order (n):	None
Harmonic(s) between 150% and 200% during more than 10% of the test time or max. 10min:	
Order (n):	None

Power Source Result

First dataset out of limit:	
DS (time):	None
Harmonic(s) out of limit:	
Order (n):	None

Average harmonic current results

Hn	leff [A]	leff [%]	Limit [A]	Result
1	1.153	100.000		
2	7.815E-3	0.678	972.00E-3	PASS
3	47.870E-3	4.151	2.07	PASS
4	3.557E-3	0.308	387.00E-3	PASS
5	16.617E-3	1.441	1.03	PASS
6	1.193E-3	0.103	270.00E-3	PASS
7	15.065E-3	1.306	693.00E-3	PASS
8	1.065E-3	0.092	207.00E-3	PASS
9	14.948E-3	1.296	360.00E-3	PASS
10	939.879E-6	0.081	165.60E-3	PASS
11	14.742E-3	1.278	297.00E-3	PASS
12	909.664E-6	0.079	138.00E-3	PASS
13	13.598E-3	1.179	189.00E-3	PASS
14	940.207E-6	0.082	118.29E-3	PASS
15	11.865E-3	1.029	135.00E-3	PASS
16	981.186E-6	0.085	103.50E-3	PASS
17	10.800E-3	0.936	119.11E-3	PASS
18	1.009E-3	0.087	92.00E-3	PASS
19	9.393E-3	0.814	106.58E-3	PASS
20	1.009E-3	0.088	82.80E-3	PASS
21	7.794E-3	0.676	96.43E-3	PASS
22	1.423E-3	0.123	75.28E-3	PASS
23	5.922E-3	0.514	88.05E-3	PASS
24	1.109E-3	0.096	68.99E-3	PASS
25	4.656E-3	0.404	81.00E-3	PASS
26	1.402E-3	0.122	63.69E-3	PASS
27	3.439E-3	0.298	75.00E-3	PASS
28	1.304E-3	0.113	59.14E-3	PASS
29	3.089E-3	0.268	69.83E-3	PASS
30	1.626E-3	0.141	55.20E-3	PASS
31	3.467E-3	0.301	65.32E-3	PASS
32	1.473E-3	0.128	51.75E-3	PASS
33	3.367E-3	0.292	61.36E-3	PASS
34	1.472E-3	0.128	48.71E-3	PASS
35	2.549E-3	0.221	57.86E-3	PASS
36	1.349E-3	0.117	46.00E-3	PASS
37	2.272E-3	0.197	54.73E-3	PASS
38	1.237E-3	0.107	43.58E-3	PASS
39	2.312E-3	0.200	51.92E-3	PASS
40	1.139E-3	0.099	41.40E-3	PASS

Maximum harmonic current results

Hn	leff [A]	leff [%]	Limit [A]	Result
1	1.230	100.000		
2	22.129E-3	1.799	2.16	PASS
3	50.741E-3	4.124	4.60	PASS
4	6.305E-3	0.512	860.00E-3	PASS
5	17.197E-3	1.398	2.28	PASS
6	2.529E-3	0.206	600.00E-3	PASS
7	16.247E-3	1.321	1.54	PASS
8	2.166E-3	0.176	460.00E-3	PASS
9	15.909E-3	1.293	800.00E-3	PASS
10	1.475E-3	0.120	368.00E-3	PASS
11	18.795E-3	1.528	660.00E-3	PASS
12	1.445E-3	0.117	306.66E-3	PASS
13	15.247E-3	1.239	420.00E-3	PASS
14	1.556E-3	0.126	262.86E-3	PASS
15	14.271E-3	1.160	300.00E-3	PASS
16	1.395E-3	0.113	230.00E-3	PASS
17	11.593E-3	0.942	264.70E-3	PASS
18	1.460E-3	0.119	204.44E-3	PASS
19	10.248E-3	0.833	236.84E-3	PASS
20	1.362E-3	0.111	184.00E-3	PASS
21	8.402E-3	0.683	214.28E-3	PASS
22	1.916E-3	0.156	167.28E-3	PASS
23	6.870E-3	0.558	195.66E-3	PASS
24	1.581E-3	0.128	153.32E-3	PASS
25	5.239E-3	0.426	180.00E-3	PASS
26	1.899E-3	0.154	141.54E-3	PASS
27	5.391E-3	0.438	166.66E-3	PASS
28	2.125E-3	0.173	131.42E-3	PASS
29	5.494E-3	0.447	155.18E-3	PASS
30	2.282E-3	0.185	122.66E-3	PASS
31	6.339E-3	0.515	145.16E-3	PASS
32	2.139E-3	0.174	115.00E-3	PASS
33	6.228E-3	0.506	136.36E-3	PASS
34	2.056E-3	0.167	108.24E-3	PASS
35	4.040E-3	0.328	128.58E-3	PASS
36	1.948E-3	0.158	102.22E-3	PASS
37	4.542E-3	0.369	121.62E-3	PASS
38	1.709E-3	0.139	96.84E-3	PASS
39	3.692E-3	0.300	115.38E-3	PASS
40	1.538E-3	0.125	92.00E-3	PASS

Maximum harmonic voltage results

Hn	Ueff [V]	Ueff [%]	Limit [%]	Result
1	231.42	100.616		
2	72.85E-3	0.032	0.2	PASS
3	81.70E-3	0.036	0.9	PASS
4	15.12E-3	0.007	0.2	PASS
5	65.77E-3	0.029	0.4	PASS
6	10.59E-3	0.005	0.2	PASS
7	52.14E-3	0.023	0.3	PASS
8	9.60E-3	0.004	0.2	PASS
9	59.51E-3	0.026	0.2	PASS
10	11.66E-3	0.005	0.2	PASS
11	44.05E-3	0.019	0.1	PASS
12	11.02E-3	0.005	0.1	PASS
13	61.22E-3	0.027	0.1	PASS
14	9.90E-3	0.004	0.1	PASS
15	37.82E-3	0.016	0.1	PASS
16	11.95E-3	0.005	0.1	PASS
17	35.83E-3	0.016	0.1	PASS
18	12.54E-3	0.005	0.1	PASS
19	35.07E-3	0.015	0.1	PASS
20	10.26E-3	0.004	0.1	PASS
21	30.75E-3	0.013	0.1	PASS
22	9.60E-3	0.004	0.1	PASS
23	36.27E-3	0.016	0.1	PASS
24	10.24E-3	0.004	0.1	PASS
25	30.95E-3	0.013	0.1	PASS
26	11.18E-3	0.005	0.1	PASS
27	45.90E-3	0.020	0.1	PASS
28	10.26E-3	0.004	0.1	PASS
29	37.30E-3	0.016	0.1	PASS
30	12.02E-3	0.005	0.1	PASS
31	44.09E-3	0.019	0.1	PASS
32	10.85E-3	0.005	0.1	PASS
33	42.44E-3	0.018	0.1	PASS
34	13.10E-3	0.006	0.1	PASS
35	32.84E-3	0.014	0.1	PASS
36	10.28E-3	0.004	0.1	PASS
37	37.30E-3	0.016	0.1	PASS
38	10.96E-3	0.005	0.1	PASS
39	21.12E-3	0.009	0.1	PASS
40	10.18E-3	0.004	0.1	PASS

Harmonic current results - DS: 12

Hn	I _{eff} [A]	I _{eff} [%]	Limit [A]	Result
1	917.174E-3	100.000		
2	3.587E-3	0.391	1.08	PASS
3	42.580E-3	4.643	2.30	PASS
4	3.385E-3	0.369	430.00E-3	PASS
5	16.190E-3	1.765	1.14	PASS
6	1.158E-3	0.126	300.00E-3	PASS
7	15.645E-3	1.706	770.00E-3	PASS
8	964.617E-6	0.105	230.00E-3	PASS
9	10.409E-3	1.135	400.00E-3	PASS
10	886.984E-6	0.097	184.00E-3	PASS
11	18.153E-3	1.979	330.00E-3	PASS
12	843.442E-6	0.092	153.33E-3	PASS
13	8.993E-3	0.981	210.00E-3	PASS
14	770.144E-6	0.084	131.43E-3	PASS
15	13.934E-3	1.519	150.00E-3	PASS
16	895.907E-6	0.098	115.00E-3	PASS
17	6.587E-3	0.718	132.35E-3	PASS
18	819.822E-6	0.089	102.22E-3	PASS
19	10.092E-3	1.100	118.42E-3	PASS
20	791.299E-6	0.086	92.00E-3	PASS
21	4.999E-3	0.545	107.14E-3	PASS
22	1.190E-3	0.130	83.64E-3	PASS
23	6.735E-3	0.734	97.83E-3	PASS
24	804.651E-6	0.088	76.66E-3	PASS
25	3.756E-3	0.410	90.00E-3	PASS
26	1.244E-3	0.136	70.77E-3	PASS
27	5.045E-3	0.550	83.33E-3	PASS
28	895.617E-6	0.098	65.71E-3	PASS
29	2.729E-3	0.298	77.59E-3	PASS
30	1.147E-3	0.125	61.33E-3	PASS
31	4.295E-3	0.468	72.58E-3	PASS
32	824.995E-6	0.090	57.50E-3	PASS
33	2.442E-3	0.266	68.18E-3	PASS
34	1.038E-3	0.113	54.12E-3	PASS
35	3.416E-3	0.372	64.29E-3	PASS
36	877.472E-6	0.096	51.11E-3	PASS
37	2.084E-3	0.227	60.81E-3	PASS
38	831.572E-6	0.091	48.42E-3	PASS
39	2.931E-3	0.320	57.69E-3	PASS
40	800.987E-6	0.087	46.00E-3	PASS

Caution: Results related to the 100% limit values

Harmonic voltage results - DS: 12

Hn	Ueff [V]	Ueff [%]	Limit [%]	Result
1	231.38	100.602		
2	67.30E-3	0.029	0.2	PASS
3	78.82E-3	0.034	0.9	PASS
4	14.58E-3	0.006	0.2	PASS
5	7.51E-3	0.003	0.4	PASS
6	4.51E-3	0.002	0.2	PASS
7	50.26E-3	0.022	0.3	PASS
8	2.73E-3	0.001	0.2	PASS
9	9.51E-3	0.004	0.2	PASS
10	9.97E-3	0.004	0.2	PASS
11	41.65E-3	0.018	0.1	PASS
12	11.02E-3	0.005	0.1	PASS
13	3.10E-3	0.001	0.1	PASS
14	4.96E-3	0.002	0.1	PASS
15	32.07E-3	0.014	0.1	PASS
16	3.98E-3	0.002	0.1	PASS
17	12.36E-3	0.005	0.1	PASS
18	7.46E-3	0.003	0.1	PASS
19	21.13E-3	0.009	0.1	PASS
20	7.30E-3	0.003	0.1	PASS
21	24.11E-3	0.010	0.1	PASS
22	6.27E-3	0.003	0.1	PASS
23	28.53E-3	0.012	0.1	PASS
24	2.34E-3	0.001	0.1	PASS
25	25.86E-3	0.011	0.1	PASS
26	3.48E-3	0.002	0.1	PASS
27	22.88E-3	0.010	0.1	PASS
28	3.39E-3	0.001	0.1	PASS
29	21.75E-3	0.009	0.1	PASS
30	10.48E-3	0.005	0.1	PASS
31	19.62E-3	0.009	0.1	PASS
32	6.88E-3	0.003	0.1	PASS
33	21.29E-3	0.009	0.1	PASS
34	3.93E-3	0.002	0.1	PASS
35	11.98E-3	0.005	0.1	PASS
36	4.42E-3	0.002	0.1	PASS
37	27.11E-3	0.012	0.1	PASS
38	650.89E-6	0.000	0.1	PASS
39	4.97E-3	0.002	0.1	PASS
40	2.64E-3	0.001	0.1	PASS

Power and THD results - DS: 12

True power P:	160.9W	Apparent power S:	200.4VA
Reactiv power Q:	47.01var	Power factor:	0.803
THD (U):	0.001	THD (I):	0.066
Crest Factor (U):	1.413	Crest Factor (I):	1.458

3.4 VOLTAGE FLUCTUATION AND FLICKERS

3.4.1 LIMITS OF VOLTAGE FLUCTUATION AND FLICKERS

Tests	Limits		Descriptions
	IEC555-3	IEC/EN 61000-3-3	
Pst	≤ 1.0, Tp= 10 min.	≤ 1.0, Tp= 10 min.	Short Term Flicker Indicator
Plt	N/A	≤ 0.65, Tp=2 hr.	Long Term Flicker Indicator
dc	≤ 3%	≤ 3.3%	Relative Steady-State V-Chang
dmax	≤ 4%	≤ 4%	Maximum Relative V-change
d (t)	N/A	≤ 3.3% for > 500 ms	Relative V-change characteristic

3.4.1.1 TEST PROCEDURE

a. Harmonic Current Test:

Test was performed according to the procedures specified in Clause 5.0 of IEC555-2 and/or Sub-clause 6.2 of IEC/EN 61000-3-2 depend on which standard adopted for compliance measurement.

b. Fluctuation and Flickers Test:


Tests was performed according to the Test Conditions/Assessment of Voltage Fluctuations specified in Clause 5.0/6.0 of IEC555-3 and/or Clause 6.0/4.0 of IEC/EN 61000-3-3 depend on which standard adopted for compliance measurement.

c. All types of harmonic current and/or voltage fluctuation in this report are assessed by direct measurement using flicker-meter.

3.4.1.2 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.1.3 TEST SETUP



3.4.2 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-11-29
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Maximum Flicker results

	EUT values	Limit	Result
Pst	0.028	1.00	PASS
Plt	0.029	0.65	PASS
dc [%]	0.006	3.30	PASS
dmax [%]	0.078	7.00	PASS
dt [s]	0.001	0.50	PASS

4. EMC IMMUNITY TEST

4.1 STANDARD COMPLIANCE/SERVIRITY LEVEL/CRITERIA

Tests Standard No.	TEST SPECIFICATION	Test Mode Test Ports	Perform. Criteria
1. ESD IEC/EN 61000-4-2	8KV air discharge 4KV contact discharge	Direct Mode	B
	4KV HCP discharge 4KV VCP discharge	Indirect Mode	B
2. RS IEC/EN 61000-4-3	80 MHz to 1000 MHz, 1.4 GHz to 2.0 GHz, 2.0 GHz to 2.7 GHz, 1000Hz, 80%, AM modulated	Enclosure	A
3. EFT/Burst IEC/EN 61000-4-4	5/50ns Tr/Th 5KHz Repetition Freq.	Power Supply Port	B
	5/50ns Tr/Th 5KHz Repetition Freq.	CTL/Signal Data Line Port	B
4. Surges IEC/EN 61000-4-5	1.2/50(8/20) Tr/Th us	L-N	B
	1.2/50(8/20) Tr/Th us	L-PE N-PE	B
5 Injected Current IEC/EN 61000-4-6	0.15 MHz to 80 MHz, 1000Hz 80% , AM Modulated 150Ω source impedance	CTL/Signal Port	A
	0.15 MHz to 80 MHz, 1000Hz 80% , AM Modulated 150Ω source impedance	AC Power Port	A
	0.15 MHz to 80 MHz, 1000Hz 80% , AM Modulated 150Ω source impedance	DC Power Port	A
6. Power Frequency Magnetic Field IEC/EN 61000-4-8	50 Hz,	Enclosure	A
7. Volt. Interruptions Volt. Dips IEC/EN 61000-4-11	Voltage dip 100%	AC Power Port	B
	Voltage dip 60%		C
	Voltage dip 30%		C
	Interruption 100%		C

4.2 GENERAL PERFORMANCE CRITERIA

According to **EN 55024 and EN 61000-6-2** standard, the general performance criteria as following:

<p>Criterion A</p>	<p>The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended.</p> <p>The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
<p>Criterion B</p>	<p>After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the equipment is used as intended.</p> <p>The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test.</p>
<p>Criterion C</p>	<p>Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions.</p> <p>Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>

4.3 GENERAL PERFORMANCE CRITERIA TEST SETUP

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

4.4 ESD TESTING

4.4.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-2
Discharge Impedance:	330 ohm / 150 pF
Required Performance	B
Discharge Voltage:	Air Discharge : 2kV/4kV/8kV (Direct) Contact Discharge : 2kV/4kV (Direct/Indirect)
Polarity:	Positive & Negative
Number of Discharge:	Air Discharge: min. 20 times at each test point Contact Discharge: min. 200 times in total
Discharge Mode:	Single Discharge
Discharge Period:	1 second minimum

4.4.2 TEST PROCEDURE

The test generator necessary to perform direct and indirect application of discharges to the EUT in the following manner:

- a. Contact discharge was applied to conductive surfaces and coupling planes of the EUT.

During the test, it was performed with single discharges. For the single discharge time between successive single discharges was at least 1 second. The EUT shall be exposed to at least 200 discharges, 100 each at negative and positive polarity, at a minimum of four test points. One of the test points shall be subjected to at least 50 indirect discharges to the center of the front edge of the horizontal coupling plane. The remaining three test points shall each receive at least 50 direct contact discharges.


If no direct contact test points are available, then at least 200 indirect discharges shall be applied in the indirect mode. Test shall be performed at a maximum repetition rate of one discharge per second.

Vertical Coupling Plane (VCP):
The coupling plane, of dimensions 0.5m x 0.5m, is placed parallel to, and positioned at a distance 0.1m from, the EUT, with the Discharge Electrode touching the coupling plane. The four faces of the EUT will be performed with electrostatic discharge.

Horizontal Coupling Plane (HCP):
The coupling plane is placed under to the EUT. The generator shall be positioned vertically at a distance of 0.1m from the EUT, with the Discharge Electrode touching the coupling plane. The four faces of the EUT will be performed with electrostatic discharge.
- b. Air discharges at insulation surfaces of the EUT.

It was at least ten single discharges with positive and negative at the same selected point.

4.4.3 TEST SETUP



Note:

TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A Horizontal Coupling Plane (1.6m x 0.8m) was placed on the table and attached to the GRP by means of a cable with 940k total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC /EN 61000-4-2, and its cables were placed on the HCP and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

FLOOR-STANDING EQUIPMENT

The equipment under test was installed in a representative system as described in section 7 of IEC/EN 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.

4.4.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	45%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Mode	Air Discharge								Contact Discharge								Criterion	Result
	4		8		10		15		2		4		6		8			
Test level (kV)																		
Test Location	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-		
HCP									A	A	A	A					B	PASS
VCP									A	A	A	A						PASS
C1									A	A	A	A						PASS
C2									A	A	A	A						PASS

Note:

- 1) +/- denotes the Positive/Negative polarity of the output voltage.
- 2) Test condition:
Direct / Indirect (HCP/VCP) discharges: Minimum 50 times (Positive/Negative) at each point. Air discharges: Minimum 10 times (Positive/Negative) at each point.
- 3) Test location(s) in which discharge (Air and contact discharge) to be applied illustrated by photos shown in next page(s)
- 4) The Indirect (HCP/VCP) discharges description of test point as following:
1.left side 2.right side 3.front side 4.rear side
- 5) N/A - denotes test is not applicable in this test report

4.5 RS TESTING

4.5.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-3
Required Performance	A
Frequency Range:	80 MHz - 1000 MHz, 1.4 GHz - 2.0 GHz, 2.0 GHz - 2.7 GHz
Field Strength:	10 V/m, 3 V/m, 1 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Polarity of Antenna:	Horizontal and Vertical
Test Distance:	3 m
Antenna Height:	1.5 m
Dwell Time:	at least 3 seconds

4.5.2 TEST PROCEDURE


The EUT and support equipment, which are placed on a table that is 0.8 meter above ground and the testing was performed in a fully-anechoic chamber.

The testing distance from antenna to the EUT was 3 meters.

The other condition as following manner:

- a. The frequency range is swept from 80 MHz to 1000 MHz, & 1400MHz - 2700MHz with the signal 80%amplitude modulated with a 1kHz sine wave. The rate of sweep did not exceed 1.5x 10⁻³ decade/s. Where the frequency range is swept incrementally, the step size was 1% of fundamental.
- b. Sweep Frequency 900 MHz, with the Duty Cycle:1/8 and Modulation: Pulse 217 Hz(if applicable)
- c. The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.
- d. The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

4.5.3 TEST SETU



Note:

TABLE-TOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC/EN 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR-STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC/EN 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

4.5.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-29
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Perform. Criteria	Results	Judgment
80MHz - 1000MHz	H / V	10 V/m (rms) AM Modulated 1000Hz, 80%	Front	A	A	PASS
			Rear			
			Left			
			Right			
1.4GHz - 2.0GHz	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	A	A	PASS
			Rear			
			Left			
			Right			
2.0GHz - 2.7GHz	H / V	1 V/m (rms) AM Modulated 1000Hz, 80%	Front	A	A	PASS
			Rear			
			Left			
			Right			

Note:

- 1) N/A - denotes test is not applicable in this test report.
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.

4.6 EFT/BURST TESTING

4.6.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-4
Required Performance	B
Test Voltage:	Power Line : 1 kV Signal/Control Line : 0.5 KV
Polarity:	Positive & Negative
Impulse Frequency:	5 kHz
Impulse Wave shape :	5/50 ns
Burst Duration:	15 ms
Burst Period:	300 ms
Test Duration:	Not less than 1 min.



4.6.2 TEST PROCEDURE

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m*1m min. and 0.65mm thick min.

The other condition as following manner:

- a. The length of power cord between the coupling device and the EUT should not exceed 1 meter.
- b. Both positive and negative polarity discharges were applied.
- c. The duration time of each test sequential was 1 minute

4.6.3 TEST SETUP



Note:

TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table (0.8m high) standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system. A minimum distance of 0.5m was provided between the EUT and the walls of the laboratory or any other metallic structure.

FLOOR-STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC/EN 61000-4-4 and its cables, were isolated from the Ground Reference Plane by an insulating support that is 0.1-meter thick. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system.

4.6.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Coupling Line		Test level (kV)								Criterion	Result
		0.5		1		2		4			
		+	-	+	-	+	-	+	-		
AC line	L	A	A	A	A	A	A			B	PASS
	N	A	A	A	A	A	A				PASS
	PE	A	A	A	A	A	A				PASS
	L+N	A	A	A	A	A	A				PASS
	L+PE	A	A	A	A	A	A				PASS
	N+PE	A	A	A	A	A	A				PASS
	L+N+PE	A	A	A	A	A	A				PASS
DC Line											
Signal Line											

Note:

- 1) +/- denotes the Positive/Negative polarity of the output voltage.
- 2) N/A - denotes test is not applicable in this test report
- 3) Criteria A: There was no change operated with initial operating during the test.
- 4) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 5) Criteria C: The system shut down during the test.

4.7 SURGE TESTING

4.7.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-5
Required Performance	B
Wave-Shape:	Combination Wave 1.2/50 us Open Circuit Voltage 8 /20 us Short Circuit Current
Test Voltage:	Power Line : 0.5 kV, 1 kV, 2 kV
Surge Input/Output:	L-N, L-PE, N-PE
Generator Source:	2 ohm between networks
Impedance:	12 ohm between network and ground
Polarity:	Positive/Negative
Phase Angle:	0 /90/180/270°
Pulse Repetition Rate:	1 time / min. (maximum)
Number of Tests:	5 positive and 5 negative at selected points

4.7.2 TEST PROCEDURE

a. For EUT power supply:

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall be 2meters in length (or shorter).


b. For test applied to unshielded unsymmetrically operated interconnection lines of EUT:

The surge is applied to the lines via the capacitive coupling. The coupling /decoupling networks shall not influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

c. For test applied to unshielded symmetrically operated interconnection /telecommunication lines of EUT:

d. The surge is applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor cannot be specified. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

4.7.3 TEST SETUP



4.7.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Coupling Line			Test level								Criterion	Result
			0.5 kV		1 kV		2 kV		4 kV			
			+	-	+	-	+	-	+	-		
AC line	L-N	0°	A	A	A	A					B	PASS
		90°	A	A	A	A						
		180°	A	A	A	A						
		270°	A	A	A	A						
	L-PE	0°	A	A	A	A	A	A				PASS
		90°	A	A	A	A	A	A				
		180°	A	A	A	A	A	A				
		270°	A	A	A	A	A	A				
	N-PE	0°	A	A	A	A	A	A				PASS
		90°	A	A	A	A	A	A				
		180°	A	A	A	A	A	A				
		270°	A	A	A	A	A	A				
DC Line												
Signal Line												

Note:

- 1) Polarity and Numbers of Impulses : 5 Pst / Ngst at each tested mode
- 2) N/A - denotes test is not applicable in this Test Report
- 3) Criteria A: There was no change operated with initial operating during the test.
- 4) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 5) Criteria C: The system shut down during the test.

4.8 INJECTION CURRENT TESTING

4.8.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-6
Required Performance	A
Frequency Range:	0.15 MHz - 80 MHz
Field Strength:	10 Vr.m.s.
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Dwell Time:	at least 3 seconds


4.8.2 TEST PROCEDURE

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m*1m min. and 0.65mm thick min.

The other condition as following manner:

- a. The frequency range is swept from 150 KHz to 80 MHz, with the signal 80%amplitude modulated with a 1kHz sine wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s. Where the frequency range is swept incrementally, the step size was 1% of fundamental.
- b. The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.

4.8.3 TEST SETUP



NOTE:

FLOOR-STANDING EQUIPMENT

The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.

4.8.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Test Ports (Mode)	Freq. Range (MHz)	Field Strength	Perform. Criteria	Results	Judgment
Input/ Output AC. Power Port	0.15 ---80	10V(rms) AM Modulated 1000Hz, 80%	A	A	PASS
Input/ Output DC. Power Port	0.15 --- 80		A	N/A	N/A
Signal Line	0.15 --- 80		A	N/A	N/A

Note:

- 1) N/A - denotes test is not applicable in this Test Report.
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.

4.9 POWER FREQUENCY MAGNETIC FIELD TESTING

4.9.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-8
Required Performance	A
Frequency Range:	50Hz
Field Strength:	30 A/m
Observation Time:	5 minute
Inductance Coil:	Rectangular type, 1mx1m


4.9.2 TEST PROCEDURE

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m*1m min. and 0.65mm thick min.

The other condition as following manner:

- a. The equipment cabinets shall be connected to the safety earth directly on the GRP via the earth terminal of the EUT.
- b. The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.

4.9.3 TEST SETUP



Note:

TABLE-TOP EQUIPMENT

The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

FLOOR-STANDING EQUIPMENT

The equipment shall be subjected to the test magnetic field by using induction coils of suitable dimensions. The test shall be repeated by moving and shifting the induction coils, in order to test the whole volume of the EUT for each orthogonal direction. The test shall be repeated with the coil shifted to different positions along the side of the EUT, in steps corresponding to 50 % of the shortest side of the coil. The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

4.9.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		

Test Mode	Test Level	Antenna aspect	Duration (s)	Perform Criteria	Results	Judgment
Enclosure	30 A/m	X	300 s	A	A	Pass
Enclosure	30 A/m	Y	300 s	A	A	Pass
Enclosure	30 A/m	Z	300 s	A	A	Pass

Note:

- 1) N/A - denotes test is not applicable in this test report
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.

4.10 VOLTAGE INTERRUPTION/DIPS TESTING


4.10.1 TEST SPECIFICATION

Basic Standard:	IEC/EN 61000-4-11
Required Performance	B (For 100% Voltage Dips) C (For 60% Voltage Dips) C (For 30% Voltage Dips) C (For 100% Voltage Interruptions)
Test Duration Time:	Minimum three test events in sequence
Interval between Event:	Minimum ten seconds
Phase Angle:	0°/45°/90°/135°/180°/225°/270°/315°/360°
Test Cycle:	3 times

4.10.2 TEST PROCEDURE

The EUT shall be tested for each selected combination of test levels and duration with a sequence of three dips/interruptions with intervals of 10 s minimum (between each test event). Each representative mode of operation shall be tested. Abrupt changes in supply voltage shall occur at zero crossings of the voltage waveform.

4.10.3 TEST SETUP



4.10.4 TEST RESULTS

EUT :	150W Enclosed Power Supply	Model Name :	ESE150-12M
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1010 hPa	Test Date :	2012-11-30
Test Mode :	Full Load		
Test Power :	AC 230V/50Hz		



Interruption & Dips	Duration (T)	Perform Criteria	Results	Judgment
Voltage dip 100%	1	B	B	PASS
Voltage dip 60%	10	C	B	PASS
Voltage dip 30%	25	C	B	PASS
Voltage dip 100%	250	C	C	PASS

Note:

- 1). N/A - denotes test is not applicable in this test report.
- 2) Criteria A: There was no change operated with initial operating during the test.
- 3) Criteria B: The EUT function loss during the test, but self-recoverable after the test.
- 4) Criteria C: The system shut down during the test.

5. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

